

SKU	SM56E			
YSTEM BUILDER SKU				
RODUCT	DIAMOND SupraMax External (Serial) 56K Modem			
PRODUCT DETAILED DESCRIPTION				
	Receive Phone Calls While Online			
	Faster Download Speeds			
	Quicker Connect Speeds     Complete Internet & Fax Solution			
	Controller-based modem for maximum performance			
	Diamond Supra unlessbas the highest performance SupraMay medame with newly adopted ITLL V 02 and V 44			
	Diamond Supra unleashes the highest performance SupraMax modems with newly adopted ITU, V.92 and V.44 compression standards.			
	SupraMax gives you the advantages of extensive analog access to the Internet with an added boost of speed over earlier standards. These improvements includes accelerated upstream data transfers (up to 40% faster), faster Internet dial-up connection times using an intelligent start-up sequence, and advanced compression algorithms that let you send commor file type (such as HTML, e-mail, and executable files) more efficiently. The new Modem-On-Hold feature lets you receive incoming voice calls without dropping your current modem connections. And, because the SupraMax V.92 is backward compatible with V.90 and earlier standards, you can relax and enjoy faster Internet speeds without worry. (For more information on V.92 features, please see below.) WHAT IS V.92? V.92 is an International Telecommunications Union (ITU) standard for analog modem connections, a new improvement over the existing V.90. Though the top speed for downloads is still 56K, V.92 has a number of enhancements.			
			WHAT FEATURES ARE INCLUDED IN V.92?	
			There are four important benefits to the V.92 standard; Quick Connect, Modem-on-hold, PCM upstream and V.44 data compression.	
	Quick Connect - by reducing the amount of time it takes for the modem and server to handshake, connect time is reduce dramatically. Instead of taking around 25 seconds to connect, this may be reduced to 8 seconds.			
	Modem-on-hold - the end user can put the modem on hold and stay connected to the Internet. The user can take an incoming voice call, or even place a call while still connected. When the call is through, the end user can resume Internet activities without having to re-dial and connect.			
	PCM upstream - increases maximum upload speed to 44 Kbps.			
	V.44 - a new standard for data compression specifically for HTML (normal website), text and other common file types, fo faster downloads. Throughput can increase up to 30-40%. This will supercede the current V.42bis standard.			
	WHAT IS REQUIRED FOR V.92 AND V.44			
	Your ISP carrier must provide support for V.92 and V.44 compression. Please consult with your ISP for details.			
	PRODUCT FEATURES	<ul> <li>Full featured data/fax external modem</li> <li>Send documents at high speeds to fax macion Supports V.92 for speeds up to 56,000 bit/s</li> <li>Sends and receives faxes with speeds up to Top-rated communications and Internet accommunications accommunications and Internet accommunications a</li></ul>	o 14,400 bit/s	
	PRODUCT SPECIFICATIONS			
RODUCT SPECIFICATIONS	<ul> <li>V.90, V.92 ITU standard 56K</li> <li>Data compression V.44, V.42bis and MNP5</li> <li>V.34 and backwards compatible protocols</li> <li>Fax speeds up to 14,400 bit/s, Group III, Class 1</li> <li>Error correction V.42 LAPM and MNP 4</li> </ul>			
YSTEM REQUIREMENT	EXTERNAL POWER REQUIREMENT			
	CPU	AMD Athlon® or Intel ® Pentium ® 4		
	CPU SPEED	486 MHZ		
	MEMORY	N/A		
	HARD DISK	5mb		
	SYSTEM BUS			
	SLOT	N/A		
	CHASSIS	N/A		
	MONITOR	Digital flat-panel (DFP) displays or DVI-I Compatilbe or		
		digital CRT display or High-resolution VGA monitor		
	INTERNET ACCESS	NO		
	USB	NO		
	CD DVD	YES		
	POWER SUPPLY	N/A		
PERATING SYSTEM	WIN98SE WINME WIN2000 WINXP LINUX32 LINUX64			
ORM FACTOR	N/A			
	[PRODUCT] : 11 13/16 X 9 1/8 X 3 1/8 [RETAIL BOX] : 11 13/16 X 9 1/8 X 3 1/8 [S BUILDER] : 12 X 7 1/4 X 2			
IMENSIONS	[PRODUCT] : 11 13/16 X 9 1/8 X 3 1/8 [RFTAIL BC			
DIMENSIONS WEIGHT JPC	[PRODUCT] : 11 13/16 X 9 1/8 X 3 1/8 [RETAIL BC [PRODUCT WEIGHT] : 0.45LBS [PRODUCT WITH RETAIL PACKAGE UPC : 018258001045			

 DIAMOND SUPRAMAX EXTERNAL (SERIAL) 56K MODEM

QUICK START GUIDE
 INSTALL CD

• TELEPHONE CABLE (RJ-11)

 PRODUCT WEBPAGE
 http://www.diamondmm.com/SM56E.php

 PRODUCT NOTES
 California Health & Safety Notice : The solder used in this product contains lead, a chemical known to the State of California to cause birth defects and other reproductive harm. Please wash hands after handling internal components and circuit boards and avoid inhalation of fumes if heating the solder.

 Diamond, Diamond Multimedia and Stealth are registered trademarks of Diamond Multimedia. ATI, Graphics by ATI, and Radeon are trademarks of ATI Technologies, Inc. AII other trademarks are property of their respective owners.
 Diamond Multimedia AG530-DeSoto Ave Chatsworth, CA 91311

 Se 2009 Diamond Multimedia. All rights reserved.
 Tel: (818) 534-1414 Fax: (818) 773-9619
 Tel: (818) 534-1414 Fax: (818) 773-9619